

VCA Headquarters 1 The Eastgate Office Centre Eastgate Road Bristol, BS5 6XX United Kingdom

Switchboard: +44 (0) 117 951 5151 Main Fax: +44 (0) 117 952 4103 Email: <u>enquiries@vca.gov.uk</u> Web: www.vca.gov.uk

THE UNITED KINGDOM VEHICLE APPROVAL AUTHORITY



COMMUNICATION CONCERNING THE APPROVAL GRANTED ⁽¹⁾/ APPROVAL EXTENDED ⁽¹⁾/ APPROVAL REFUSED ⁽¹⁾/ APPROVAL WITHDRAWN ⁽¹⁾/ PRODUCTION DEFINITELY DISCONTINUED ⁽¹⁾ OF A TYPE OF MECHANICAL COUPLING DEVICE OR COMPONENT, PURSUANT TO REGULATION NO 55.01 SUPPLEMENT 2

Approval No: 55R-019582

Extension No: 01

- 1. Trade name or mark of the device or component: V. ORLANDI Spa
- 2. Manufacturer's name for the type of device or component: OC68R
- Manufacturer's name and address:
 V. Orlandi Spa
 Via Quinzano 3
 I 25020 Flero (BS)
 Italy
- 4. If applicable, name and address of the manufacturer's representative: Not applicable
- 5. Alternative supplier's names or trade marks applied to the device or component: Not applicable
- 6. Name and address of company or body taking responsibility for the conformity of production: See item 3. above
- 7. Submitted for approval on: 28 May 2012
- 8. Technical service responsible for conducting approval tests: TÜV SÜD Automotive GmbH
- 9. Brief description: Non standard drawbar eye
 - 9.1. Type and class of device or component: S



- 9.2. Characteristic values:
 - 9.2.1. Primary values:
 - D: 200 kN
 Dc: 120 kN
 S: 1000 kg

 U.....tonnes
 V: 60 kN

 Alternative values:
 D...... kN
 S...... kg

 U......kN
 Dc....... kN
 S...... kg
 - 9.3. For Class A mechanical coupling devices or components, including towing brackets: Not applicable

Vehicle manufacturer's maximum permissible vehicle mass: kg

Distribution of maximum permissible vehicle mass between the axles:

Vehicle manufacturer's maximum permissible towable trailer mass: kg

Vehicle manufacturer's maximum permissible static mass on coupling ball: kg

Maximum mass of the vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied) but not including driver: kg

Loading condition under which the tow ball height of a mechanical coupling device fitted to category M_1 vehicles is to be measured -see paragraph 2 of annex 7, appendix 1:

- 9.4. For class B coupling heads, is the coupling head intended to be fitted to an unbraked O_1 trailer: Not applicable
- 10. Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points given by the vehicle manufacturer: See manufacturers documentation
- 11. Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component: Not applicable
- 12. Additional information where the use of the coupling device or component is restricted to special types of vehicles see annex 5, paragraph 3.4. Not applicable
- 13. For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type. Not applicable
- 14. Date of test report: 28 May 2012



- 15. Number of test report: 12-00277-CX-GBM Extension 01
- 16. Approval mark position: On drawbar eye body
- 17. Reason(s) for extension of approval: To cover1) Addition of Dc, S and V value2) Updated mounting instruction
- 18. Approval GRANTED/EXTENDED/REFUSED/WITHDRAWN⁽¹⁾
- 19. Place: BRISTOL
- 20. Date: 03 JULY 2012

8ten-21. Signature:

A. W. STENNING Head of Technical and Quality Support Group

22. The list of documents deposited with the Administration Service which has granted approval is annexed to this communication and may be obtained on request.

(1) Strike out what does not apply.

